Secknell Model C3235

Waterproof Check Weigher





The C3235 is a waterproof NSF check weigher for the rapid indication of weight and over, under, accept tolerances in washdown environments.

Available in a choice of 6 lb / 3 kg, 12 lb / 6 kg and 30 lb / 15 kg capacities with resolution of 1 part in 6000 the C3235 is ideal for portion controlling, food processing and catering kitchens applications.

Simple to operate the keyboard has four buttons – off, on/zero, push button tare and function. The function key gives access to the check weigher set up for targets and tolerances (LED and audible alarm), unit switching and count modes.

A battery charge indicator is built in to the display giving an instant check on the condition of the battery.



Within 0.05% at full load



Power Internal main/AC adapter and rechargeable battery (approx. 20 hours)



Capacity 6 lb x 0.02 oz / 3 kg x 0.5 g 12 lb x 0.05 oz / 6 kg x 1 g 30 lb x 0.1 lb / 15 kg x 2 g



Six digit, 0.5" / 13 mm high seven segment bright red LED display accept, over, under LED



VALUE IN WEIGHING

Construction

Washable and corrosion free ABS/stainless steel housing with food safe stainless steel weight platter Occor Operator Keys Off, Zero, Function, Tare

Specifications

Capacity:

6 lb x 0.001 lb / 3 kg x 0.5 g 12 lb x 0.002 lb / 6 kg x 1 g 30 lb x 0.005 lb / 15 kg x 2 g

Platform Dimension (L x W x H) 9" x 7 ½" x 0.5" 229 mm x 190 mm x 13 mm

Construction: Rugged ABS plastic lower housing, stainless steel upper housing (IP66) and stainless steel weighing platter

Display: Sealed watertight seven segment, six digit, 0.5" / 13 mm high red LED with annunciators

Annunciators: kg, g, lb, oz, tare, over, under, accept, count, zero, and battery voltage

Keyboard: On/Zero, Off, Tare, Function. The function key gives access to checkweigh targets (with audible alarm), unit switching and count.

Unit: lb, lb/oz, kg, g

Functions: Count, unit switching, check weigh limits with alarm, auto off after 10 minutes of inactivity

Power: Internal main/AC adapter and rechargeable battery (6V - 4.5Ah)

Battery Life: Approximately 20 hours (charge time is 12 hours)

Operating Temperature: 23° F to 95° F / -5° C to 35° C

Scale Dimension (L x W x H): 9.25" x 11" x 4" / 235 mm x 285 mm x 110 mm

Platform Dimension (L x W x H): 7.5" x 9" x 0.5" / 190 mm x 229 mm x 13 mm

Weight: 8 lb / 3.7 kg

Packaging Dimension (L x W x H): 13.25" x 11" x 5.75" 337 mm x 280 mm x 146 mm

Shipping Weight: 10 lb / 4.5 kg

Certifications: NSF, full FCC compliance, Prop 65, CEC, UL approved power adapter





brecknellscales.com brecknellscales.co.uk

Part of Avery Weigh-Tronix

Brecknell is part of Avery Weigh-Tronix. Avery Weigh-Tronix is a trademark of Illinois Tool Works group of companies whose ultimate parent company is Illinois Tool Works Inc. ("Illinois Tool Works:). Copyright © 2023 Illinois Tool Works. All rights reserved. This publication is issued to provide outline information only and may not be regarded as a representation relating to the products or services concerned. This publication was correct at the time of going to print, however Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service at any time.